# Rockwater 1



# The Rockwater 1 is a diving vessel.

- Length 98m x breadth 18m
- Deck area 550m²
- Accommodation for 94 persons plus 15 divers in saturation
- 120t crane
- 18-man\* single bell saturation dive system with one hyperbaric lifeboat
- 1 x observation class ROV

# Rockwater 1



#### **General Information**

Classification LR, +100A1, LMC, DP(AA)

UMS, Ice-class 3

Built de Hoop, Netherlands (1983) Flag State Authority Bahamas Maritime Authority

Port of Registry Nassau

#### **Dimensions**

 Overall Length
 98.35m

 Breadth
 18m

 Depth
 7.6m

 Draught (summer)
 5.3m

 Deadweight
 1,900t

 Gross Tonnage
 4,905t

 Net Tonnage
 1471t

#### **Manoeuvring and Propulsion Systems**

Main Engines 5 x 1,700kW (Brons-MAN

ASL25/30)

Generators 5 x 2125 kVA (NEBB WAB 630)

Emergency Generator 1 x GM Type 12v-72t Main Propulsion 2 x 1,880kW azimuth thrusters (Liaanen)

# **Dynamic Positioning Systems**

Tunnel Thrusters (bow)

DP Classification DP(AA) (Class II)

ERN Rating 99.99.99

DP System Konsberg Simrad SDP 521

Reference Systems 2 x DGPS

2 x lightweight taut wire

3 x 7,90kW (Brunvoll)

1 x HiPAP 350

1 x Sonardyne/Ranger Fusion 1 x fanbeam 4.1 (1,000m range)

# **Speed / Consumptions**

Economical Speed 10 knots at 18m³/per day Full Speed 12.5 knots at 24m³/per day

DP Operations 14m³/per day

# Tank Capacities (100%)

 Fuel Oil
 1,263m³

 Fresh Water
 385m³

 Ballast Water
 923m³

 Lub. Oil
 30m³

# Cargo Deck

Deck Area 550m<sup>2</sup>
Deck Strength 5t/m<sup>2</sup>

### **Deck Cranes**

Main Deck Crane 120 tonne Hydramarine

(MacGREGOR)

HMC 3568 crane

Mainline (AHC) SWL 120 tonnes at 5 to 12m

(Double Line)

SWL 60 tonnes at 6.5m to 25m

(Single Line)

Whipline SWL 15 tonnes at 7 to 32m Whipline (man riding) SWL 7.5 tonnes at 7 to 32m

Auxiliary Deck Cranes

Guerra (Heli-deck Area)

Z-Marine (Gas Storage Area) SWL 7.5 tonnes - 10m

SWL 5 tonnes - 14.5m SWL 1.25 tonnes

#### **ROV Systems**

The vessel is fitted with one Lynx observation ROV with hydraulic manipulator and water jetting skid as standard.

## **Dive System**

The saturation diving system is classed by Lloyds Register of Shipping.

Saturation System 16 man at 300m

\*(restricted to 15 due to SPHL)

Chambers 3

 Bell
 1 x (3 diver)

 SPHL
 1 x 15 man

 Dive Moonpool
 3.6m x 3.6m

### **Accommodation**

94+15\* persons

Single Cabins 18
Double Cabins 38
Divers in SAT\* 15
Hospital

(not included in total)

#### Helideck

The vessel is fitted with an approved and certified helideck. The helideck has a D value of 22 and is approved for Sikorsky S61N helicopters.

### **Communications Systems**

The vessel is fitted with Fleet 7 Inmarsat Vsat Satellite communications. The Vsat can be either KU band or C band as operational requirements demand.



on the state of th

www.subsea7.com